



## Specifications

Rev s.r

### Design

- x Computer aided design/Computer aided manufacturing - CAD/CAM
- x Patented designs with other patents pending
- x Precision laser cut and powder coated painted parts with infused labels directions
- x Modular components and assembly for quality, reliability and ease of repair and maintenance
- x Both natural turf and artificial turf - indoor and outdoor
- x Painting, grooming, spraying, fence line, weed removal, and utility capabilities
- x Removal of painted lines, logos, end zones on synthetic and natural turf

### Propulsion System

- x Engine V-Twin Cylinder
  - f Honda GX630 20.8 hp
- x Fuel System
  - f 6 gal. Capacity, 5 gal. Main, 1 gal. reserve, aluminum fuel tank with tethered gas cap
- x Hydraulics
  - f Parker hoses and fittings with dual filtration
  - f Propel pump
    - f Infinitely variable, bidirectional, axial piston pump design
    - f Direct coupled, tandem configuration, with auxiliary accessory pump
  - f Wheel Motors
    - f 2 Fixed displacement, bi-directional, high torque orbital wheel motors
    - f Rated 7250 lb. rear axle capacity
  - f Auxiliary pump
    - f Positive displacement, gear pump
    - f 6CM<sup>3</sup>/rev and 5.46 GPM
  - f Cooling system for hydraulics
    - f Aluminum hydraulic fluid heat exchanger. Augments engine compartment cooling.
    - f 12V, 5.4A fan 280 CFM
    - f 8" x 8" x 4.5"
  - f Hydraulic fluid tank with sight gauge and internal filter
    - f 5.4 gal. system capacity
  - f Wheels and tires
    - f Front 16 x 17.5 - 8 low ground pressure 4 ply TurfTech
    - f Rear 23 x 10.50 - 12 low ground pressure 4 ply TurfTech
  - f Forward speed variable 13 MPH – reverse speed variable 3 MPH

### Electrical System

- x Voltage / Amperage – 12V, 20 ampere charge
- x Battery – 340CCA / 425CA
- x 12V accessory receptacle - charger port
- x Gauge package, hour meter, volt meter, paint PSI
- x All harness wirings color - coded for ease of maintenance and troubleshooting
- x High quality connectors - commercial soft shell pin and socket
- x Modular assemblies for ease of maintenance and troubleshooting

## Paint /Water/Chemical Tank and Spraying System

- Top quality hoses and fittings
- Brass regulator / stainless steel internals
- Kromer engineered Hypro Ultra Pressure Paint Pump 290 PSI 6 GPM
- Built in storage compartment and cup holder

Ultra pressure paint system can save up to 50% in paint costs

### Paint systems options

- Low Pressure dust control electric pump system
  - Hash line marker
  - Soccer arm attachment for painting circles.
  - Ezy Fast Fill™ system transfer pump pumps paint directly from a 5 gal. 70 lb paint pail into main tank. Transfer pump also decreases viscosity of paint, making easier to mix with water.
- 
- **Tank system**
    - 65 gal. capacity
    - Custom patented design 62.5 gal. paint / water / chemical capacity
    - Durable corrosion proof high quality rotomolded plastic
    - Integral 2.5 gal. fresh water rinse tank (tank within a tank)
    - Easy outboard fill location for both tanks
      - Quick lock lid on main tank
      - Double filtration (basket filter, in-line bowl filter / strainer)
      - In-tank agitation
    - 100% positive drain sloped sump system
    - Cleans systems 3 ways
      - Water hose flush main tank
      - Connect water hose to inlet selector valve
      - Clean paint nozzles, paint lines and paint pump with integral fresh water tank in about 2 minutes

## Ergonomics

- Large operator compartment - increased steering wheel clearance, large foot wells, improved design accelerator foot pedal
- Upgraded seat with lumbar support and adjustable weight suspension.
- Main painter head – foot operated lift assist (greatly reduced effort - 72% reduction)
- All controls clearly marked
  - Special process image infused graphics lasting durable powder coat finish
  - Easy to read color coded grouped controls and receptacles

## Versatility

- Many painting options and accessories - Custom modifications available

## Dimensions

- Main tractor without options or accessories
  - Weight 989 LBS - Length 82.6" - Width 45.6" - Height 52.3"

## Warranty

- 3 yr. Limited Warranty, 3 yr. Manufacture Engine